

FLEXBOND

LATEX-BASED LIQUID ADMIXTURE (CONCENTEATE)

FlexBond replaces some or all of the water in cement mixes to improve bond, waterproofing, flexural, tensile & abrasive strengths, adhesion, thin film hardness, weak acid resistance, adhesion to asphalt & reduce drying shrinkage. It can be used to waterproof water-containing structures. And used in conjunction with textiles & membranes for cracks & joints in structures.

PURPOSE

Replaces the water in cement mixtures.

APPLICATION

Add to cement mixtures.

CURING

Needs to air cure for at least 12 hours when mixed with

cement.

PACKAGING

1, 5 & 20 litre containers.

COVERAGE

Dependant on what it's mixed with. See datasheet for more information.

APPEARANCE / COLOUR(S)

Milky white liquid.



BENEFITS

- Compatible with Portland cement, High Alumina cement, lime & sand
 - Offers exceptional adhesion for various applications
 - Non-flammable
- Unaffected by damp conditions; mixtures may be applied to damp surfaces
 - Improves freeze / thaw resistance of cement mixes
 - Improves chemical resistance
 - Sold undiluted, therefore offering a more economical choice
- Offers colour enhancement & pool chemical resistance when added to PoolCrete
- FlexBond has multiple uses speak to a Cemcrete representative for more information



info@cemcrete.co.za www.cemcrete.co.za







in



HEAD OFFICE

Showroom & Warehouse & Telford Street Industria (011) 474 2415 info@cemcrete.co.za

GAUTENG

Johannesburg Showroom

227 Jan Smuts Avenue Parktown North (011) 447 3149 jsa@cemcrete.co.za

Centurion Showroom & Warehouse

15 Coachmen's Park 26 Jakaranda Street Centurion (012) 653 6808 pretoria@cemcrete.co.za

CAPE TOWN

Showroom & Warehouse

Unit 3 Eagle Park cnr Bosmansdam & Omuramba Roads Montague Gardens (021) 555 1034 cape@cemcrete.co.za

We have distributors both nationally and internationally. Contact us to locate your nearest retailer or contractor.



Creating distinctive cement finishes

as unique as you are.